MINIBLUE®





PERFORMANCE

1) 21 dba

| MAX FLOW | MAX HEAD | MAX LIFT |
|-----------|----------|----------|
| 8 L/ HOUR | 8 METRES | 5 METRES |

Running either wet or dry, the MINIBLUE® is whisper quiet whilst reliably removing condensate and debris. Inherently reliable whilst self priming it gives peristaltic performance at the price of a piston pump. The MINIBLUE® is small enough to quickly fit, or retro fit, into any existing installation, saving both time and money.

SENSING OPTION

MINIBLUE® pump available with:

| CR PLUG | TEMPERATURE SENSOR |
|---------|-----------------------|
| X87-500 | X87-504 |
| | |




All of the BLUEDIAMOND® pumps have the ability to run dry without burning out. Enabling them to remove any liquids, preventing organic growth inside the tubing.



Quiet in all stages of operation and not only when set to quiet mode or relying on a soft start setting.


UNIT 3.5-8 KW


PERFORMANCE



DIMENSIONS (MM)

V (VERTICAL)





H (HORIZONTAL)

DISCHARGE PIPE RUN



| 8 M | 0 M |
|-----|------|
| 7 M | 3 M |
| 6 M | 6 M |
| 5 M | 9 M |
| 4 M | 12 M |
| 3 M | 15 M |
| 2 M | 18 M |
| 1 M | 21 M |

The MINIBLUE® can be mounted in any orientation up to 8m away from the A.C unit.

